

# HEAVY-DUTY TILE & GROUT CLEANER

## DESCRIPTION:

AQUA MIX HEAVY-DUTY TILE & GROUT CLEANER is a concentrated, high-alkaline cleaner and degreaser. Effectively removes grease, soap scum, body oil, mildew stains, and algae from areas that have been neglected or subjected to heavy use. Specially formulated to strip off synthetic and acrylic waxes and floor finishes.

Aqua Mix Low VOC (Volatile Organic Compound Formulas) help provide better indoor and outdoor air quality compared to similar traditional products. 25 grams of VOC's per liter of material.

## USES:

Natural stone (such as granite, limestone, slate, and travertine), ceramic, porcelain, quarry, Saltillo, terra cotta, cement pavers, masonry surfaces, linoleum, or resilient flooring.

## TEST A SMALL AREA:

According to application instructions to determine desired results.

## APPLICATION:

### DO NOT KNEEL IN THIS PRODUCT. AVOID ALL SKIN CONTACT.

- 1) Read entire label before using.
- 2) Put on Rubber Gloves and Eye Protection.
- 3) Sweep, vacuum, or wipe surface.
- 4) Mix Heavy-Duty Tile & Grout Cleaner as follows: LIGHT SOIL BUILD-UP: Mix 1 part cleaner to 5 parts water. MODERATE SOIL BUILD-UP: Mix 1 part cleaner to 3 parts water. STRIPPING OR HEAVY SOIL BUILD-UP: Mix 1 part cleaner to 2 parts water.
- 5) Apply solution to surface with mop or sponge.
- 6) Allow to dwell 3 to 5 minutes for cleaning, or 5 to 10 minutes when stripping waxes or finishes.
- 7) Agitate with synthetic mop, scrub brush, or scrub machine. Do not allow solution to dry on surface.
- 8) Mop up dirty solution.
- 9) Rinse thoroughly with clean water.

## LIMITATIONS:

- Do not allow product to come in contact with any non-recommended surface.
- May adversely affect grout joints that have been coated with colorant or grout stain.
- Regular use of high alkaline cleaners will reduce sealer life.

## HANDLING AND STORAGE:

- Close container after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F and 90 °F (4 °C and 32 °C).

## CAUTION:

CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED. Wear skin and eye protection. Do not breathe vapor or spray. Contains sodium hydroxide and ethylene glycol monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

## KEEP OUT OF REACH OF CHILDREN

**LIMITED PRODUCT WARRANTY** Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

### COVERAGE:

Approximately 150 to 600 sq. ft. (15 m<sup>2</sup> to 55 m<sup>2</sup>) per gallon (3.8 L) depending on dilution.

## ORDERING INFORMATION:

Item Code US	Item Code Canada	Size	Package
010382-4	C010382-4	1 Qt.	Bottle
010383	C010383	1 Gal.	Bottle
010384*	C010384	5 Gal.	Pail

\*Indicates a special order item.