

MATERIAL SAFETY DATA SHEET

Spectrum 2000 Sanded Caulk

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

1. Product And Company Identification

Supplier CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com	Manufacturer CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com
Supplier Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980	Manufacturer Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980

Issue Date: 02/20/2007

Product Name: Spectrum 2000 Sanded Caulk

CAS Number: Not Established

Chemical Formula: Mixture

MSDS Number: 847

Product Code: SKO63

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
SILICA, Quartz, Crystalline	14808-60-7	1 - 10

3. Hazards Identification

Primary Routes(s) Of Entry

Eye , Skin Contact, Inhalation and Ingestion.

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

If swallowed it may cause gastrointestinal irritation.

Inhalation Hazards

vapors or spray mist may cause nose irritation.

MATERIAL SAFETY DATA SHEET

Spectrum 2000 Sanded Caulk

3. Hazards Identification - Continued

Chronic/Carcinogenicity Effects

This product contains silica sand, a known human carcinogen. The sand is encapsulated in the caulk and thus rendered harmless until released into air by mechanical abrasion.

Conditions Aggravated By Exposure

Over exposure may cause skin, nose, throat and respiratory tract irritation.

Conditions Aggravated By Overexposure

4. First Aid Measures

Eye

Gently blot or wipe any residue remaining on the face, being careful not to get it in the victim's eyes or on skin. Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin

Remove excess from the skin. Wash skin with plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel. Get medical attention immediately. If there is any discomfort from ingestion, consult a physician.

Inhalation

If inhaled, remove to fresh air. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: NONE °F

Flash Point Method: NONE

Lower Explosive Limit: 3.2%

Upper Explosive Limit: N/A

Fire And Explosion Hazards

Material will not burn until all water has evaporated. Cans may burst open and splatter material if temperatures reach 212 deg F and above.

Extinguishing Media

Foam, CO2, Dry chemical, Water fog.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. material will not burn but may splatter if temperature exceeds boiling point. Dried material will burn and may give off carbon and nitrogen oxides.

6. Accidental Release Measures

Clean up spill immediately. Cover with absorbent to contain. Collect and dispose. Use appropriate containers to avoid environmental contamination. Avoid runoff to waterways and sewers. Avoid release to the environment. Use appropriate personal protective equipment (PPE).

7. Handling And Storage

Handling And Storage Precautions

Store in cool, dry areas away from sunlight, heat and heat sources. Protect from freezing.

MATERIAL SAFETY DATA SHEET

Spectrum 2000 Sanded Caulk

7. Handling And Storage - Continued

Work/Hygienic Practices

Wash thoroughly with soap and water after handling. Use good personal hygiene. Observe good housekeeping practices.

8. Exposure Controls/Personal Protection

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

General room ventilation is normally adequate. In case of inadequate ventilation, use NIOSH-approved respirator.

Other/General Protection

General ventilation is usually sufficient. Fan or other device maybe needed if used in small and enclosed areas.

Ingredient(s) - Exposure Limits

SILICA, Quartz, Crystalline
ACGIH TLV-TWA 0.05 mg/m³
OSHA PEL-TWA 30/%SiO₂+2mg/m³
OSHA PEL - TWA 10/% SiO₂ +2 mg/m³
OSHA PEL-TWA 250/%SiO+5 mppcf
Cal EPA - OEHHA - REL - 3 micrograms/m³

Adequate clothing to prevent skin contact.

9. Physical And Chemical Properties

Appearance

Viscous liquid.

Odor

Mild ammonia odor.

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 212 °F 100 °C

Specific Gravity: 1.4

Percent VOCs: 5%

Vapor Density: HEAVIER THAN AIR

pH Factor: 8

Solubility: Dilutable in water

Viscosity: Water like

Evaporation Rate: Slower than ether

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Protect from freezing.

MATERIAL SAFETY DATA SHEET

Spectrum 2000 Sanded Caulk

10. Stability And Reactivity - Continued

Incompatible Materials

Avoid contact with strong oxidizers.

Hazardous Decomposition Products

Thermal decomposition in air may result in carbon monoxide and / or carbon dioxide.

Conditions To Avoid (Polymerization)

Hazardous polymerization will not occur. Heat may cause pressure build-up in closed containers

11. Toxicological Information

Chronic/Carcinogenicity

This product contains silica sand, a known human carcinogen. The sand is encapsulated in the caulk and thus rendered harmless until released into air by mechanical abrasion.

Ingredient(s) - Carcinogenicity

SILICA, Quartz, Crystalline
NTP - Listed On The National Toxicology Program
Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations and industry standards.

RCRA Information

Not considered RCRA waste

14. Transport Information

DOT Shipping Label

Not Regulated

15. Regulatory Information

Ingredient(s) - U.S. Regulatory Information

SILICA, Quartz, Crystalline
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical
SARA - Chronic Health Hazard

Ingredient(s) - State Regulations

SILICA, Quartz, Crystalline
New Jersey - Workplace Hazard
Pennsylvania - Workplace Hazard
California - Proposition 65
Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: B

MATERIAL SAFETY DATA SHEET

Spectrum 2000 Sanded Caulk

16. Other Information - Continued

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (562) 968-2980 ext 103

This MSDS Supersedes A Previous MSDS Dated: 02/08/2007

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000